



Tragfähigkeits- & Geschwindigkeitstabelle*

LI	kg	LI	kg	LI	kg	LI	kg	LI	kg	LI	kg	Symbol	km/h
19	77,5	50	190	81	462	112	1120	143	2725	174	6700	A1	5
20	80	51	195	82	475	113	1150	144	2800	175	6900	A2	10
21	82,5	52	200	83	487	114	1180	145	2900	176	7100	A3	15
22	85	53	206	84	500	115	1215	146	3000	177	7300	A4	20
23	87,5	54	212	85	515	116	1250	147	3075	178	7500	A5	25
24	90	55	218	86	530	117	1285	148	3150	179	7750	A6	30
25	92,5	56	224	87	545	118	1320	149	3250	180	8000	A7	35
26	95	57	230	88	560	119	1360	150	3350	181	8250	A8	40
27	97,5	58	236	89	580	120	1400	151	3450	182	8500	B	50
28	100	59	243	90	600	121	1450	152	3550	183	8750	C	60
29	103	60	250	91	615	122	1500	153	3650	184	9000	D	65
30	106	61	257	92	630	123	1550	154	3750	185	9250	E	70
31	109	62	265	93	650	124	1600	155	3875	186	9500	F	80
32	112	63	272	94	670	125	1650	156	4000	187	9750	G	90
33	115	64	280	95	690	126	1700	157	4125	188	10000	J	100
34	118	65	290	96	710	127	1750	158	4250	189	10300	K	110
35	121	66	300	97	730	128	1800	159	4375	190	10600	L	120
36	125	67	307	98	750	129	1850	160	4500	191	10900	M	130
37	128	68	315	99	775	130	1900	161	4625	192	11200	N	140
38	132	69	325	100	800	131	1950	162	4750	193	11500	P	150
39	136	70	335	101	825	132	2000	163	4875	194	11800	Q	160
40	140	71	345	102	850	133	2060	164	5000	195	12150	R	170
41	145	72	355	103	875	134	2120	165	5150	196	12500	S	180
42	150	73	365	104	900	135	2180	166	5300	197	12850	T	190
43	155	74	375	105	925	136	2240	167	5450	198	13200	U	200
44	160	75	387	106	950	137	2300	168	5600	199	13600	H	210
45	165	76	400	107	975	138	2360	169	5800	200	14000	V	240
46	170	77	412	108	1000	139	2430	170	6000	201	14500	VR	>210
47	175	78	425	109	1030	140	2500	171	6150	202	15000	W	270
48	180	79	437	110	1060	141	2575	172	6300	203	15500	ZR	>240
49	185	80	450	111	1090	142	2650	173	6500	204	16000	Y	300

*=Für Fehler keine Haftung